


SPECIFICATIONS

MPU600

Bottom Mount Cabinet Chiller



SPECIFICATIONS

Refrigeration system	Electronic controlled, self-contained, top mounted, refrigeration unit	
Refrigerant	R134a / 270g	
Nominal capacity	440 Watts @ -10°C SST	
Cabinet internal volume	600 litres	
Insulation	60mm thick, high density, Zero ODP injected polyurethane insulation	
Cabinet temperature range	-2°C to +4°C up to 43°C ambient	
Drainage	Waste heat vaporiser located in service compartment (no plumbing required)	
Electrical	240 Volts a.c. 50 Hz, 1.8 Amps	
kWh/24hr	N/a	
Internal door opening size	1 door opening: Accepts full 1/1 & 2/1 GN pans	
Doors	Stainless steel, self-closing, lockable solid door (Reversible)	
Shelves	4 shelves & adjustable tray slides per door (325mm wide x 350mm deep)	
Weight	128kg	
Cabinet dimensions	External	Internal
Width	720mm	600mm
Depth	825mm	675mm
Height	1900mm*	1480mm

OPTIONS

- Glass doors
- Half drawers
- Legs
- Extra shelves
- Extra slides
- ST/ST back
- Heli-coil Cable
- Hydrocarbon Refrigerant

* Height excludes castors or legs